The enclosed data are based on a concentration of 4% QUORAL BR and testing at 25 °C. We always recommend carrying out specific tests.

+	=	g	0	0	C

+ = good			
	-		
Acetic Acid	+	Ink	++
Acetone	++	Isopropanol	++
Benzene	++	Ketones	++
Brake Fluid	+	Linseed Oil	++
Butane	++	Lubrication Oil	++
Chlorobenzene	++	Methane	++
Chlorodefluoroethylene	++	Methanol	+
Chlorodefluoromethane	++	Methyl Ethyl Ketone	++
Citrus Oils	++	Methyl Glycol	+
Cyclohexane	++	Monochloroethyl Acetate	++
Cyclohexanol	++	Monochoromethyl Acetate	++
Cyclohexanone	++	Naphthalene	++
Dichlorobenzene	+	Nitrobenzene	++
Dichloroethane	+	Paint Solvents	++
Dichlorofluoromethane	++	Palm Oils	+
Dichlorotetrafluoroethane	++	Paraffin Oil	+
Dioxan	++	Paraxylene	+
Edible Fats and Oils	++	Phenol	++
Ethanol	++	Polyglycols	++
Fats and Waxes, edible	++	Propanol	+
Fatty Acids	++	Pyridine	++
Fatty Alcohols	++	Shellsol A/AB	++
Fruit Juices	++	Silicone Oils	++
Fuel, Diesel	++	Solvesso 100/150	++
Fuel, Gasoline	++	Sulfolane	+
Gear Oil	++	Terpenes	++
Glycerol	++	Tetralin	++
Grease	++	Thinner	+
Heptane	++	Toulene	++
Hexachloroethane	++	Trichloreothylene	++
Hexachlorobenzene	++	Trichlorotrifluoroethane	++
Hexane	++	Triethanolamine	++
Hydraulic Fluid	++	Turpentine	+
Hydraulic Oil	+	Xylene	++



No legal guarantee or obligation may be inferred from this information, whether for specific properties or for suitability for a particular application.

This table should be used as a reference, but does not exempt the user from carrying out individual tests and trials. It is the shipper's responsibility for ensuring proper compatibility and verifying compliance with applicable laws and regulations.