



Lithium Metal Batteries

Section II

Cell/Battery lithium content:	≤ 0.3 g	0.3 g – 1.0 g	0.3 g – 2.0 g
Max. # cells/batteries per package:	No limit	8 cells	2 batteries
Maximum net quantity per package:	2.5 kg	N/A	N/A
Maximum number of packages per shipment:	1 package		
Packaging:	<ul style="list-style-type: none"> ▪ Inner packaging must completely enclose each cell/battery (and prevent contact between multiple cells/batteries) ▪ Strong rigid outer packaging - batteries must be protected from damage/compression (drum, jerrican, or box) ▪ Package must be capable of withstanding a 1.2 m drop test in any orientation, without: damage, shifting, or release of contents. 		
Documentation:	<ul style="list-style-type: none"> ▪ Shipper’s Declaration is NOT required ▪ A document is required, indicating: <ul style="list-style-type: none"> - the package contains lithium metal cells or batteries; - the package must be handled with care & a flammability hazard exists if the package is damaged; - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; - a telephone number which can be called for additional information 		
Air Waybill:	<ul style="list-style-type: none"> ▪ “Lithium metal batteries in compliance with Section II of PI 968” & “CAO” must be included in the ‘nature & quantity of goods’ box. 		
Labelling:	<p>Package must be labeled with the lithium (metal) battery handling label and Cargo Aircraft Only label:</p> <div style="display: flex; justify-content: center; gap: 20px;">   </div>		